INSTALLATION INSTRUCTIONS SIDEBAR PART # 201001/201001-2 1999-2004 GRAND CHEROKEE 2/4WD

PARTS LIST:

Qty	Description	Qty	Description
1	Driver Side/left side bar	8	1/2" x 1 1/4" Hex Bolts
1	Passenger Side/right side bar	4	1/2" x 2" Hex Bolts
2	Driver & Passenger Front Mounting Bracket	12	1/2" Flat Washers
2	Driver & Passenger Rear Mounting Bracket	12	1/2" Lock Washers
4	Thread Nut Plates		





Page 1 of 2

PROCEDURE:

1. REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT. READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION.

- 2. Starting with the Driver/left side Proceed with your install (refer to Fig 1)
- 3. From parts list above select Driver/left side sidebar,(Note: step pad closest to the end of tube go to rear of vehicle, attach both Front and Rear mounting Brackets to Side Bar using (1) 1/2" x 2" Hex Bolt,(1) 1/2" Flat washer & (1) 1/2" Lock washer for each mount bracket. Snug but do not tighten hardware at this time.
- **4.** Slide the Nut plate into vehicles front suspension mount & secure the front mounting bracket to the nut plate with (2) 1/2" x 1 1/4" Hex bolts, (2) 1/2" flat washers, (2) 1/2" lock washers. Snug but do not tighten hardware at this time.
- 5. Secure the rear mounting bracket to the vehicles rear suspension mount in the same manner. Snug but do not tighten hardware at this time.
- 6. Align Sidebar properly, and then tighten all hardware.
- 7. Repeat steps 2 6 for the passenger Sidebar.
- 8. Do periodic inspections to the installation to make sure that all hardware is secure and tight.

To protect your investment, wax this product after installing. Regular waxing is recommended to add a protective layer over the finish. Do not use any type of polish or wax that may contain abrasives that could damage the finish.

For stainless steel: Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap may be used also to clean the Sidebar.

For gloss black finishes: Mild soap may be used to clean the Sidebar.

DRIVER SIDE SIDEBAR

