



(888) 800-ARIES
824 E. Anaheim St., Ste A
Wilmington, CA 90744

Part No. 201002, 201002-2

Application: 2002-05 JEEP LIBERTY SPORT, LIMITED

PARTS LIST

<u>ITEM</u>	<u>DESCRIPTION</u>	<u>QUANTITY</u>
1.	STEP BAR ASSEMBLY, PASSENGER SIDE	1
2.	STEP BAR ASSEMBLY, DRIVER SIDE	1
3.	FRONT MOUNT BRACKET, PASSENGER	1
4.	FRONT MOUNT BRACKET, DRIVER	1
5.	REAR MOUNT BRACKET, PASSENGER	1
6.	REAR MOUNT BRACKET, DRIVER	1
7.	BOLT PLATE	6
8.	PLASTIC WASHER	6
9.	3/8-16 X 1.00" BUTTON HEAD CAP SCREW	8
10.	3/8" INTERNAL TOOTH LOCK WASHER	8
11.	1/2" FLAT WASHER	8
12.	1/2" SPLIT LOCK WASHER	8
13.	1/2"-13 HEX NUT	6
14.	5/8" FLAT WASHER	2
15.	M12-1.75 HEX NUT	2

TOOLS REQUIRED

<u>ITEM</u>	<u>DESCRIPTION</u>	<u>QUANTITY</u>
1.	3/4" SOCKET	1
2.	19MM COMBINATION WRENCH	1
3.	7/32" HEX WRENCH (ALLEN)	1
4.	RATCHET	1
5.	TORQUE WRENCH	1

INSTALLATION INSTRUCTIONS

STEP 1

Remove the contents from the box and check for any damage. Verify all parts against the parts list.

STEP 2

Read and understand instructions completely before beginning installation.

STEP 3

Determine driver front and rear mount brackets. Locate mount holes on frame for front and rear brackets. For rear mount location, install (1) bolt plate through large hole on bottom of frame into small hole on side of frame and use (1) plastic washer to hold in place. For front mount location, insert (2) bolt plates through large hole so that they protrude through smaller holes adjacent and use (2) plastic washer to hold in place. **See figure 1.**

STEP 4

Position driver rear bracket in place with (1) 5/8" flat washer above bracket as a spacer. Fasten 12mm stud and 1/2" bolt plate using (1) 1/2 -13 hex nut, (1) M12 -1.75 hex nut, (2) 1/2" flat washer and (2) 1/2" lock washer. Leave fasteners loose.

STEP 5

Position driver rear bracket in place to the bolt plates using (2) ½” flat washer, (2) ½” lock washer, and (2) ½” -13 hex nut. Leave loose.

FINISH PROTECTION- ARIES PRODUCTS HAVE A HIGH FINISH THAT MUST BE MAINTAINED SUCH AS ANY OTHER HIGH FINISH PRODUCT ON THE VEHICLE. PROTECT THE FINISH WITH A NON-ABRASIVE AUTOMOTIVE WAX. THE USE OF SOAP, POLISH, OR WAX THAT CONTAINS ABRASIVES IS DETRIMENTAL, AS THE COMPOUNDS SCRATCH THE FINISH AND OPEN IT TO CORROSION.

DISCLAIMER- BUYER ASSUMES ALL RISK AND LIABILITY WHATSOEVER FROM THE INSTALLATION AND USE OF ARIES PRODUCTS. ARIES PRODUCTS ARE SOLD AS DECORATIVE ACCESSORIES AND SHOULD NOT BE RELIED UPON AS PROTECTION FOR THE VEHICLE OR OCCUPANTS IN THE EVENT OF A COLLISION OR ROLL OVER. ARIES AUTOMOTIVE ASSUMES NO LIABILITY FOR INJURY, LOSS, INCIDENTAL OR CONSEQUENTIAL DAMAGES IN THE EVENT OF A COLLISION OR ROLLOVER.

