INSTALLATION INSTRUCTIONS

1976-06 CJ / YJ Wrangler Front Tubular Bumpers 2007-11 JK Wrangler Front Tubular Bumpers 2007-11 Wrangler license plate relocator used with 15600 bumper PART # 55-0000

PARTS LIST:

Qty	Description	Qty	Description
1	License plate relocator	1	8mm x 35mm Hex bolt
1	Nut plate mounting bracket	1	8mm lock washer
1	8mm x 75mm Hex bolt	4	6.5mm ID X 20mm OD flat washers
4	6mm x 20mm button head bolts		



Nut plate mounting	bracket
O)

PROCEDURE:

- 1. REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT. READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION.
- 2. Start by placing the nut plate behind the bumper with the nut facing to the back, once insert Attach & secure the License plate relocator with (1) 8mm lock washers & (1) 8mm x 75mm Hex bolt as seen in (Fig 1) Level and adjust the license plate relocator to the bumper and tighten all hardware attaché your license plate with (4) 6mm button head bolts & (4) 6.5mm flat washers.

To protect your investment, wax this product after installing. Regular waxing is recommended to add a protective layer over the finish. Do not use any type of polish or wax that may contain abrasives that could damage the finish.



PROCEDURE:

3. REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT. READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION.

4. Start by inserting the nut plate into the opening on the bumper, as seen in (Fig 1) once insert as seen in (Fig 2) Attach & secure the License plate relocator with (1) 8mm lock washers & (1) 8mm x 35mm Hex bolt as seen in (Fig 3) Level and adjust the license plate relocator to the bumper and tighten all hardware attaché your license plate with (4) 6mm button head bolts & (4) 6.5mm flat washers.

To protect your investment, wax this product after installing. Regular waxing is recommended to add a protective layer over the finish. Do not use any type of polish or wax that may contain abrasives that could damage the finish.



